

PICO

Top Feed Injector



Description

The "Pico" top feed injector is a standard production component built to the same automotive standard and specification.

The characteristics of the injector are a fast pulse response, high precision, high dynamic range and optimum fuel atomisation. These are achieved by a high performance ON-OFF actuating electromagnet with opposing expansion poles that moves an internal injector valve on high-precision ground cylindrical slides, and a high precision nozzle.

The injector has a stainless steel body, a fuel-resistant plastic connector, martensitic stainless steel internal valve and an electromagnet with a low carbon content stainless steel armature.

The electrical connection to the control unit is via a Mini-Timer plastic plug.



Technical Data

Performance - Typical

Linearity range (Tj = 4 ms)± 2.5 %
Max. fuel pressure allowed.....500 kPa
Maximum duty cycle.....90 %
Operating temperature range-30...110 °C
Vibration (peak).....30 g

Test conditions

Fluid..... N-Heptane
density (@ 20°C)0.684 kg/litre
Ambient and fluid temperature23 °C
Power supply14 Vdc
Injection frequency Fully open
Pulse durationn/a
Pressure 3 bar

Mechanical Characteristics


Height.....47.2 mm
Outside diameter (connector excluded) .. 15.3 mm
Weight.....35 g

Electrical Characteristics

Connector Mini-Timer 2 way
Power supply 8 ÷ 16 Vdc
Resistance..... 14.5 Ω
Driver type ON-OFF

Electrical connections

PIN	Description
1	GND
2	+12 V



Ordering information

Part No	Description	Colour band	Order code
IWP 001	Pico injector – 200 cc/min static flow		214310000110
IWP 006	Pico injector – 226 cc/min static flow	Blue	214310000610
IWP023	Pico injector – 158 cc/min static flow	Green	214310002310
IWP043	Pico injector – 329 cc/min static flow	Brown	214310004310
IWP045	Pico injector – 200 cc/min static flow		214310004510
IWP049	Pico injector – 184 cc/min static flow		214310004910
IWP064	Pico injector – 186 cc/min static flow		214310006400
IWP069	Pico injector – 491 cc/min static flow	Yellow	214310006900

For further details please contact

MM Competition Systems Ltd
Hyjuniper, Long Lane
Shaw, Berkshire,
RG14 2TA
England

Tel: +44 (0)8707 444666
Fax: +44 (0)8707 444888
www.mmcompsys.com
mail@mmcompsys.com