

<b>Multistrada 1200 Enduro Pro</b>	
<b>Engine</b>	
Engine	Ducati Testastretta DVT with variable valve timing, L-Twin cylinder, 4 valves per cylinder, Dual Spark, liquid cooled
Displacement	1,198.4 cc
Bore X stroke	106 x 67.9 mm
Compression ratio	12.5:1
Power	112 kW (152 hp) * @ 9,500 rpm
Torque	128 Nm (94 lb-ft) @ 7,500 rpm
Fuel injection	Bosch electronic fuel injection system, elliptical throttle bodies with Ride-by-Wire, equivalent diameter 56 mm
Exhaust	Stainless steel muffler with catalytic converter and 2 lambda probes, Ducati Performance by Termignoni single titanium muffler
<b>Trasmission</b>	
Gearbox	6 speed
Primary drive	Straight cut gears; Ratio 1.84:1
Ratio	1=38/14 2=30/17 3=27/20 4=24/22 5=23/24 6=22/25
Final drive	Chain; Front sprocket 15; Rear sprocket 43
Clutch	Light action, wet, multiplate clutch with hydraulic control. Self-servo action on drive, slipper action on over-run
<b>Chassis</b>	
Frame	Tubular steel Trellis frame
Front suspension	Sachs 48 mm fully adjustable usd forks. Electronic compression and rebound damping adjustment with Ducati Skyhook Suspension (DSS)
Front wheel	Tubeless spoked wheel in light alloy 3" x 19"
Front tyre	Pirelli Scorpion Rally 120/70 R19
Rear Suspension	Fully adjustable Sachs unit. Electronic compression & rebound damping adjustment. Electronic spring pre-load adjustment with Ducati Skyhook Suspension (DSS) Evo. Aluminium double-sided swingarm
Rear Wheel	Tubeless spoked wheel in light alloy 4.50" x 17"
Rear tyre	Pirelli Scorpion Rally 170/60 R17
Wheel travel (front/rear)	200 mm - 200 mm (7.87 in - 7.87 in)
Front brake	2 x 320 mm semi-floating discs, radially mounted monoblocco Brembo callipers, 4-piston, 2-pad, with cornering ABS as standard equipment
Rear brake	265 mm disc, 2-piston floating calliper, with cornering ABS as standard equipment
Instrumentation	Colour TFT display 5"
<b>Dimensions and weights</b>	
Dry weight	232 kg (511 lb)
Kerb weight	261 kg (575 lb)
Seat height	870 mm (34.25 in)
Wheelbase	1,594 mm (62.76 in)
Rake	25°
Front wheel trail	110 mm
Fuel tank capacity	30 l - 7.9 gallon (US)
Number of seats	Dual seat
<b>Standard equipment</b>	
	Vehicle Hold Control (VHC), Riding Modes, Power Modes, Ride by Wire (RbW), Ducati Safety Pack (Bosch Cornering ABS + DTC), Ducati Skyhook Suspension (DSS) Evo, Ducati Wheelie Control (DWC), Cruise control, Full LED headlamp with Ducati Cornering Lights, Hands-Free, Backlit handlebar switches, Ducati Multimedia System (DMS), Full-colour TFT display, Ducati Performance by Touratech side tank protectors, Ducati Performance by Termignoni single titanium muffler, LED additional lights, low windscreen, Steering damper, Anti-theft ready
<b>Warranty</b>	
Warranty (months)	24 months unlimited mileage
Maintenance (km/months)	15,000 km (9,000 miles) / 12 months
Valve clearance adjustment (km)	30,000 km (18,000 miles)
<b>Emissions and consumption</b>	
Standard	Euro 4
Consumption	5.6l/100 km - CO2 132 g/km

\* The power/torque values indicated are measured using an engine dynamometer according to homologation regulation and they correspond to the homologated data, as quoted in the Bike Registration Document.